


# **DISCUS Workshop**

## **Refining a Nanoparticle with Least Squares Algorithm**

Reinhard B. Neder  
Crystallography and Structural Physics  
Friedrich-Alexander-Universität Erlangen-Nürnberg

[reinhard.neder@fau.de](mailto:reinhard.neder@fau.de)



# Refining a Nanoparticle

Goal:


**Refine Size/shape of  
ellipsoidal Gold nanoparticle  
decorated with a simple ligand**


Basic Info:

**Input data**

**Refinement parameters**

A quick demonstration





# Refining a Nanoparticle

Open in Windows Explorer:

Start DISCUS\_SUITE

Lectures\  
07\_Refinement\  
REFINE\_ELLIPSOID


**You should see:**

...  
User macros in ...  
System macros in ...  
Start directory ...

suite >


suite > **cd Lectures\07\_Refinement\REFINE\_ELLIPSOID**

suite > **@refine.mac**




# Refining a Nanoparticle

```
refine refine.mac  
data xy, DATA/gold.grobs ! Refine against these data
```




```
#Data in gold.grobs  
X Y Sigma(x) sigma(y)
```

Must be larger than zero!




# Refining a Nanoparticle

```
refine          refine.mac
data xy, DATA/gold.grobs      ! Refine against these data
#
newparam P_lat      , value:4.0102, range:[3.95,4.20], &
                        status:free, points:5, shift:0.003
```





<b>P_lat</b>	Any valid DISCUS variable name	
<b>value:</b>	Initial <b>value</b> for this refinement parameter	Required
<b>range:</b>	Upper and lower limit [low , high]      [low , ]      [ , high ]	Optional
<b>status:</b>	Refine value or keep it fixed	Defaults to <b>free</b>



# Refining a Nanoparticle


Least-Squares needs derivatives:

$$\partial G_{\text{r}}/\partial P_{\text{lat}} = \text{value}$$




Refine calculates derivatives numerically

- More **points**: better accuracy for derivative; yet more computation time
- Larger **shift**: Necessary for parameters that change the function in discrete steps  
For continuous parameters, a smaller shift gives better estimate




# Refining a Nanoparticle

```
refine          refine.mac
data xy, DATA/gold.grobs      ! Refine against these data
#
newparam P_lat      , value:4.0102, range:[3.95,4.20], &
                        status:free, points:5, shift:0.003
```




<b>P_lat</b>	Any valid DISCUS variable name	
<b>value:</b>	Initial <b>value</b> for this refinement parameter	Required
<b>range:</b>	Upper and lower limit [low , high]      [low , ]      [ , high ]	Optional
<b>status:</b>	Refine value or keep it fixed	Defaults to <b>free</b>
<b>points:</b>	number of points for derivative	Defaults to <b>3</b>
<b>shift:</b>	Relative parameter change	Defaults to <b>0.003</b>




# Refining a Nanoparticle

```
refine                refine.mac  
data xy, DATA/gold.grobs    ! Refine against these data  
#  
newparam P_lat      , value:4.0102, range:[3.95,4.20],  &  
                        status:free, points:5, shift:0.003  
#  
set cycle, 25          ! Maximum cycle number  
set relax, start, 2.000 ! Start value for Lambda parameter
```




**relax:** Control how much a parameter is changed from cycle to cycle  
Large LAMBDA => small changes






# Refining a Nanoparticle

```
refine                               refine.mac
data xy, DATA/gold.grobs           ! Refine against these data
#
newparam P_lat                      , value:4.0102, range:[3.95,4.20], &
                                   status:free, points:5, shift:0.003
#
set cycle, 25                        ! Maximum cycle number
set relax, start, 2.000              ! Start value for Lambda parameter
#
set conver, dchi:0.5, pshift:0.005, conf:0.90, chisq:1.1
#set conver, status:off
```




**convergence:** Control termination criteria converged if:

- dchi:** If  $\chi^2$  changes by less
- pshift:** If largest relative parameter change is less
- conf:** If confidence number is larger
- chisq:** If  $\chi^2$  is less




# Refining a Nanoparticle

```
refine                refine.mac
data xy, DATA/gold.grobs      ! Refine against these data
newparam P_lat      , value:4.0102, range:[3.95,4.20], &
                        status:free, points:5, shift:0.003
set cycle, 25                ! Maximum cycle number
set relax, start, 2.000 ! Start value for Lambda parameter
set conver, dchi:0.5, pshift:0.005, conf:0.90, chisq:1.1
#
run discus_main.mac, plot:k_inter.mac
```




**run:** start calculation, use macro *discus\_main.mac* to calculate  
optionally show current status with plot macro *k\_inter.mac*



# Refining a Nanoparticle

## discus\_main.mac

```
branch discus          ! 1st line must branch
#
calc_calc_calc         ! calculate desired function
#
branch kuplot          ! Sidestep into kuplot
load xy, CALC/gold.grcalc ! Make sure calculated function is
#                      ! last data set
exit                   ! back to DISCUS
exit                   ! BACK TO REFINE
finished               ! Special REFINE command to indicate End of
```




Slave macro must start with a branch.

Last data set in kuplot must be the calculated function.


Exit back to refine.

The **finished** command indicates to refine that this is the end of the slave macro




# Refining a Nanoparticle

```
reset                k_inter.mac      ! We are in kuplot already
load xy, DATA/gold.grobs             ! Original data
load xy, CALC/gold.grcalc             ! Calculated function
kcal sub, 1, 2                        ! Difference Obs-Calc
r[0]= min(-1,nint(min(ymin[1],ymin[2]) - ymax[3]))
ccal add, wy, 3, r[0]                 ! Shift difference curve down
scale xmin[1], xmax[1], ymin[3]*1.025, max(ymax[1],ymax[2])*1.025
mark 5, 5                           ! Scale section and place markers
lcol 3, black                        ! Difference curve in black
plot                               ! Display actual graph
rval 1, 2, dat                       ! Display R-value
exit                                 ! Back to refine
```



Plot macro automatically starts within kuplot.  
May do a reset within kuplot.  
Exit back to refine.



# Refining a Nanoparticle

Open in Windows Explorer:

Start DISCUS\_SUITE

Lectures\  
07\_Refinement\  
REFINE\_ELLIPSOID

## You should see:


...  
User macros in ...  
System macros in ...  
Start directory ...

suite >

suite > **cd Lectures\07\_Refinement\REFINE\_ELLIPSOID**

suite > **@refine.mac**

Try with :    different start values  
              small values for shift => cover, diameter



# Refining a Nanoparticle

---